

DOUGLAS ATTACK-BOMBER 8A-5

MAKE THE RADIO MAST FROM
SCRAP
BALSA.

HARDWOOD NOSE PLUG IS
REMOVABLE

CARVE THE COWL FROM A VERY SOFT
AND LIGHT BALSA BLOCK $2\frac{1}{8} \times 2\frac{1}{8} \times 2\frac{5}{8}$.
HOLLOW THE COWL TO THE WALL THICK-
NESS SHOWN BY THE BROKEN LINE.

THIN CELLULOID
WINDSHIELD

$\frac{1}{16}$ " SHEET

BLACK
PAPER

WING
OUTLINE

"LINE-UP"
LONGERON

CENTER
SECTION
RIB

NOTE THE $\frac{1}{16}$ "
SHEET "FILL-IN" AT
WING-FUSELAGE
JOINT.

COWL BULKHEAD
HARD $\frac{1}{8}$ " SHEET

MAKE THE CENTER
SECTION RIBS FROM $\frac{1}{16}$ " SHEET
BALSA. SEVEN ARE REQUIRED.

THE WING FILLET IS
SHOWN IN DOTTED LINE.

WING FILLET

MAKE THE WING
FILLET FROM $\frac{1}{64}$ "
SHEET BALSA. 2 REQ'D.

$1\frac{3}{8}$ " DIAMETER
BALSA WHEELS.

PROPELLER

SIDNEY STRUHL '41