



ASSEMBLY INSTRUCTIONS

FUSELAGE

1. Cut wood from wing as shown, groove edges 1/32\" x 1/32\" x 1/32\" on inside & epoxy. (See photo for wire.)

2. Glue wire through the fuselage for the landing gear wire. Drill a hole through the 3/32\" hole through the fuselage for the landing gear wire. Drill a hole through the 3/32\" hole through the fuselage for the landing gear wire. Drill a hole through the 3/32\" hole through the fuselage for the landing gear wire.

WING

1. Cut the center piece of the wing from the center of the wing. Cut the center piece of the wing from the center of the wing. Cut the center piece of the wing from the center of the wing.

2. Glue the wing to the fuselage. Glue the wing to the fuselage. Glue the wing to the fuselage.

FINISHING

1. Sand the fuselage. Sand the fuselage. Sand the fuselage.

2. Paint the fuselage. Paint the fuselage. Paint the fuselage.

INCH DIMENSIONS DO NOT SCALE DRAWING		THIRD ANGLE PROJECTION	
UNLESS STATED, TOLERANCES ON DIMENSIONS ARE			
FRACTIONAL	+/- TOLERANCE	ANGLE	+/- TOLERANCE
1-1/2"	± .01	90°	± .1°
1-1/2"	± .01		
1-1/2"	± .01		
1-1/2"	± .01		

MACLEAN RACING

TORONTO, CANADA

NAME: MIKE ARGANDER SPECIAL
"A", "B" AND "AA"
CLASS: GOODYEAR RACER